

# EcoRange

## EcoRO-2500 Reverse Osmosis



*EcoRO is a high-performing reverse osmosis system. Generate high purity water streams, safely, efficiently and effectively using the latest state of the art low energy membranes.*

EcoRO-2500 Reverse Osmosis units produce from 3,100 to 6,200 l/hr flow rates of high purity water for pharmaceutical, electronics, boiler feed and general manufacturing applications.

Reverse Osmosis (RO) is a broad purification process, removing a high proportion of most impurities. The systems can remove up to 98% of dissolved inorganics and over 99% of total dissolved organics, colloids and particles.

The flexible design of the EcoRO Reverse Osmosis systems can accommodate different membranes to suit different applications.



## Features and Benefits

- High efficiency, low energy membranes
- Low operating costs and total cost of ownership, particularly when used with Envirogen consumables
- Pre-packaged, skid-mounted system minimises installation, commissioning and start-up time
- Easy operation with a simple-to-use control panel
- Removal of 99% of suspended and colloidal solids, dissolved ions and organic compounds
- Removal of 99.9% of viruses, bacteria and pyrogens
- Built with high quality components and fully stainless steel versions to meet hygienic conditions
- Bespoke configurations to meet every requirement
- Options for water softener feed and antiscalant dosing
- Nationwide network of after sales service and support ensures that your water systems are maintained in optimal operational condition efficiency thus reducing operating costs
- Up to 90% water recovery option

## Additional Features

- Clean in place (CIP) unit
- Membrane monitoring
- Remote service monitoring options
- Automatic conductivity and or timer controlled membrane flushing

## Technical Specification

Range/Model		EcoRO-2510	EcoRO-2520	EcoRO-2530	EcoRO-2540
Capacity*	l/hr	3100	4300	5100	6200
Maximum recovery	%	75	75	75	75
Salt rejection	%	96-98	96-98	96-98	96-98
Typical water quality*	µS/cm	<30	<30	<30	<30
Electrical Supply	V/Hz	3x400/50	3x400/50	3x400/50	3x400/50
Power consumption	kW	5.5	5.5	5.5	5.5
Inlet pipe diameter	inches	1 1/2	1 1/2	1 1/2	1 1/2
Concentrate outlet diameter	inches	1 1/4	1 1/4	1 1/4	1 1/4
Permeate outlet diameter	mm	1	1	1	1
Feed water pressure	bar	3/7	3/7	3/7	3/7
Dimensions: Depth	mm			1300	
Dimensions: Width	mm			780	
Dimensions: Height	mm			1630	
Maximum water temp	°C	25	25	25	25

\*Depends on the feedwater quality. The stated data is nominal and based on a potable feed water supply with a maximum total dissolved solids level of 500 mg/l, a minimum temperature of 10°C and a 3 bar inlet pressure.

**UK Headquarters**  
**Envirogen Group**  
 Unit 9, Wimsey Way  
 Alfreton Trading Estate  
 Alfreton  
 Derbyshire  
 DE55 4LS  
 T: +44 1773 441 029

**The Netherlands Office**  
**Envirogen Technologies bv**  
 Penningweg 71  
 1507 DG Zaandam  
 Netherlands  
 T: +31 75 204 7200  
 E: ninfo@enviroengroup.com

**Germany (Sales)**  
 T: +49 234 6220 9001  
 E: info.de@enviroengroup.com

**Italy (Sales)**  
 T: +39 029 39 591  
 E: info.it@enviroengroup.com

**North American Headquarters**  
**Envirogen Technologies Inc**  
 2627 Chestnut Ridge Rd.,  
 Suite 260  
 Kingwood, TX 77339  
 T: 877.312.8950  
 E: info@envirogen.com