


EcoRange

EcoSoft Water Softener



The Envirogen Group EcoSoft range covers flow rates from 0.4 to 20 m³/hr. EcoSoft delivers a cost efficient, flexible and easy-to-use solution to the problems associated with hard water.

The EcoSoft range uses high quality vessels and high efficiency softening resin to provide high quality softened water, reduce salt usage and reduce waste water. Typical applications include partial softening of drinking water in domestic applications, service water, process water, boiler feed water and cooling water applications.



Features and Benefits

- Pre-packaged, skid-mounted system minimises installation, commissioning and start-up time
- Cost-effective design using high efficiency resin to reduce salt and waste water
- Simplex and Duplex options
- Fully automatic operation requiring minimal operator involvement
- Flexible system with options for immediate or delayed regeneration (i.e. regenerate overnight or during periods of no demand)
- Simple control system operating on low voltage to ensure safe installation and operation.
- Service friendly design (minimal down time)
- Nationwide network of after sales service and support ensures that your water systems are maintained in optimal operational condition efficiency thus reducing operating costs

Technical Specification

Range/Model		ECS-10	ECS-30	ECS-50	ECS-75	ECS-125	ECS-200	ECS-250	ECS-350	ECS-500
Resin Volume	L	10	30	50	75	125	200	250	350	500
Normal Flow Rate (at 1 bar ΔP)	m ³ /hr	0.4	1.2	2.0	3.0	5.0	8.0	10	14	20
Min Flow Rate	m ³ /hr	0.06	0.06	0.06	0.06	0.06	0.06	0.12	0.34	0.34
Max Flow Rate	m ³ /hr	6.1	6.1	6.1	6.1	6.1	7.7	13.7	26.0	26.0
Treated water m ³ at 300 ppm CaCO ₃	m ³	1.7	5.0	8.3	12.5	20.8	33.3	41.7	58.3	83.3
Salt Consumption	kg/regen	1.5	4.5	7.5	11.3	18.8	30.0	37.5	52.5	75.0
Water used per regen	L	143	238	224	397	455	814	1513	1345	2320
Treated Water Hardness	mg/l	<10	<10	<10	<10	<10	<10	<10	<10	<10

System Dimensions, Weights and Connections

Range/Model		ECS-10	ECS-30	ECS-50	ECS-75	ECS-125	ECS-200	ECS-250	ECS-350	ECS-500
Control Valve Size	-	1"	1"	1"	1"	1"	1.25"	1.5"	2"	2"
System Height	mm	622	1080	1580	1590	1870	1980	1830	2100	2270
Recommended Headroom	mm	1000	1000	1000	1000	1000	1000	1000	1000	1000
System Width: - Simplex	mm	550	600	720	1031	1059	1390	1442	1500	1810
System Width: - Duplex	mm	900	1130	1130	1610	1840	1960	2190	2290	2670
Weight (*): - Simplex	Kg	13	40	65	90	140	230	275	400	555
Weight (*): - Duplex	Kg	35	75	115	180	280	450	461	534	1109
Connection In & Out (BSP)	inches	1"	1"	1"	1"	1"	1" or 1.25"	1.5"	2"	2"
Drain Connection Standard	inches	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	1.5"	1.5"
Drain Connection Optional	inches	1"	1"	1"	1"	1"	1"	1"	N/A	N/A

*Estimated weight of the system without water or salt

Feed Water Supply Quality

Potable water free from organic contamination, chlorine and suspended solids.

Supply Pressure: unpressurised via local break tank.

Temperature: min. 5°C / max. 30°C

Electrical Supply

All models 240v, single phase, 6W power

UK Headquarters

Envirogen Group

Unit 9, Wimsey Way
Alfreton Trading Estate
Alfreton
Derbyshire
DE55 4LS
T: +44 1773 441 029
E: enquiries@envirogen.com

The Netherlands Office

Envirogen Technologies bv

Penningweg 71
1507 DG Zaandam
Netherlands
T: +31 75 204 7200
E: ninfo@envirogen.com

Germany (Sales)

T: +49 234 6220 9001
E: info.de@envirogen.com

Italy (Sales)

T: +39 029 39 591
E: info.it@envirogen.com

North American Headquarters

Envirogen Technologies Inc

2627 Chestnut Ridge Rd.,
Suite 260
Kingwood, TX 77339
T: 877.312.8950
E: info@envirogen.com